

## Rail Traction Supplies D 20W/40 LZF Lub Oil (Product Code RTS/D20/40 LZF)



### Description

A high performance zinc-free railroad diesel engine lubricant meeting LMOA4 requirements, suitable for naturally aspirated and turbocharged diesels running on low sulphur fuel.

### Benefits

- Long life zinc-free lubricant.
- Good wear and corrosion protection.
- Suitable for naturally aspirated and turbocharged diesel running on low sulphur fuel.
- Meets GE and EMD approval

### Application

The sulphur in fuel should not exceed 1.0%wt.

### Typical Data

Appearance		Amber
Specific Gravity	@ 15°C	0.896
Kinematic Viscosity	@ 40°C cSt	137.6
Kinematic Viscosity	@ 100°C cSt	15.2
Viscosity Index		112
Viscosity Apparent	-15°C, mPa.s	9200
HTHS	150°C, mPa.s	4.16
Pumpability	-20°C, mPa.s	33400
Pour Point (°C)		-12
Flash Point (°C)		248
Noack volatility, %wt		5.9
TBN (mg KOH/gram)		13.3
Sulphated ash (% weight)		1.54

October 2009

Rail Traction Supplies Ltd

[www.railtractionsupplies.co.uk](http://www.railtractionsupplies.co.uk)

[sales@railtractionsupplies.co.uk](mailto:sales@railtractionsupplies.co.uk)